



249.00 EUR
incl. 19% VAT, plus [shipping](#)

- Fanless !
- Auto Power On/Off !
- e13 certified !
- WLAN/GPS/GPRS !

Support: [Drivers \(Win\)](#) | [Drivers \(Linux\)](#) |  [GPS/GSM/GPRS Setup \[EN\]](#)

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition :
- 2.5" HDD/SSD or CompactFlash

The PC is completely fanless and is equipped with an Intel Celeron Mobile (M440) 1.83Ghz CPU and 1GB RAM.

Project orders:

The system also is available with other CPUs (eg. T2500/T7400/...). And you can get 2GB RAM. The system also can be shipped without GPS, WLAN and/or GSM/GPRS option. It is also possible to extend warranty time to 3-5 years. Contact us !

Features :

- Fanless
- Intel Socket P Mobile CPU Support
- Integrated, intelligent Automotive power supply
- 2x RS232
- 2x Gigabit LAN
- DSUB-15 VGA + DVI
- Watchdog
- GPS, WLAN, GSM/GPRS with ext. antennas
- 8bit GPIO
- EMark 13 and vibration/shock tested

| | |
|---------------------|--|
| Dimensions / Weight | 279mm W x 176mm D x 67mm H, 2.9kg |
| CPU | Socket M (support Intel Core 2 Duo/Core Duo/Celeron M) [Intel Celeron-M 1.86Ghz included] |
| Chipset / FSB | Intel 945GME + Intel ICH7M , 533/667Mhz FSB |
| RAM | 1x SO-DDR-2 RAM (up to 2GB 533/667) [1GB RAM included] |
| Graphics | Intel GMA 950 |
| Expansion | - 1x PCI-104 module slot - Internal USB WLAN module [Included] - Internal RS232 GPRS/GSM module COM3 [Included] - Internal RS232 GPS module COM4 [Included] |

| | |
|-----------------------|--|
| OS Support | Windows XP Home/Pro/Embedded, Linux FC 6/7 |
| Vibration | IEC 60068-2-64 5~500Mhz 2GRMS for CF, 3GRMS for SSD |
| Shock | IEC 60068-2-27 50G-500m/s ² -11ms |
| Operating temperature | -20~60°C (with Industrial grade CF) |
| Certification | CE, FCC class B, EMark 13 |
| I/O | <ul style="list-style-type: none"> - 2x LAN (Broadcom BCM5787) - 4x RS232 (2x DB9, 2x internal used for GPS+GPRS) - 4x USB2.0 (3x external, 1x internal used for WLAN) - 8bit GPIO (4 in, 4 out) - 1x PS/2 - Mic-In, SPK Out - 1x Remote power control - 15A Fuse for 12V, 0.5A for 24V - 1x VGA (DSUB-15) - 1x DVI - 3x Antenna hole (GPS, GSM/GPRS, WLAN) |
| Drive bays | <ul style="list-style-type: none"> 1 x Anti-Shock 2.5" HDD bracket (for IDE-44pin or SATA II) 1 x External CF slot (Type I/II) |
| Power supply | <ul style="list-style-type: none"> 9~32V DC PSU included (90W max) - Fuse design - Power on/off retry - Adjustable delay time for system OFF by switch - System on/off by vehicle ignition or remote switch button - Low power input monitoring, Auto Shutdown |
| Scope of supply | <ul style="list-style-type: none"> FleetPC-3 PC with Intel Celeron-M 440 (1.86Ghz), 1GB RAM, mounting bracket - Quickstart-Guide, DriverCD - Remote switch cable - Replacement fuse f. 24V - HDD bracket and screws - SATA data cable, SATA power cable - WLAN, GPRS and GPS antennas - PS/2 Splitter cable - 2x mounting-metal brackets |