



137.00 EUR  
incl. 19% VAT, plus [shipping](#)

**Support:**  [Specifications \[EN\]](#)

- VIA VX800 Chipset
  - Support VIA C7 1.5GHz(90nm,FSB 400MHz,1.5GHz) processor
  - Integrated Chrome9 HC3 DX9 IGP
  - Integrated LVDS support 24-bit TFT LCD
  - Support 1 x 32-bit PCI slot
  - Support 2 x Serial ATA 2 Devices
  - Windows Vista Ready
  - Onboard Gigabit LAN
  - Support DC FAN
  - COM2 Support RS422/485
  - VIA VT1708B HD Audio Codec with 6-Channel
  - 170 x 170mm Mini-ITX Form Factor
  - Support Daughter board Expansion
  - Support Watch dog Technology
- |                    |  |
|--------------------|--|
| 1. CPU             | 1. Support VIA C7 1.5GHz(90nm,FSB 400MHz,1.5GHz) processor                   |
|                    | 2. Front Side Bus 400MHz   |
| 1. Chipset         | 1. VIA VX800 Chipsets  |
|                    | 2. VIA Chrome9 HC3 IGP, 128Bit 3D engines( Share System Memory:64/128/256MB) |
| 1. Memory          | 1. 1 * 240-pin DIMM Sockets for un-buffered DDR2 667MHz SDRAM up to 2GB      |
| 1. Expansion Slots | 1. 1 * 32-bit PCI slots  |

- 1. **Power Management**      1. ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature
- 1. **Storage**                    1. 2 \* Serial ATA2 3Gb/s connectors with RAID 0,1 functions
- 2. 1 \* Ultra DMA 133/100/66 IDE connector
- 1. **Audio**                        1. VIA VT1708B HD Audio Codec with 6-Channel
- 1. **Ethernet LAN**                1. 1 \* RTL8111C 10 / 100 / 1000 PCI LAN
- 1. **USB**                            1. Embedded 6 \* USB 2.0/1.1
- 1. **LVDS**                            1. Onboard 24-bit dual channel LVDS connector
- 2.
- 1. **Rear Panel I / O**            1. 2 \* USB 2.0/1.1 ports
- 2. 1 \* PS/2 connector for Keyboard and Mouse
- 3. 1 \* RJ-45 ports
- 4. 3 \* Audio I/O ports ( Line-in, mic and line-out )
- 5. 1 \* VGA port
- 6. 1 \* DB-9 RS232 COM port
- 1. **Internal I / O**                1. 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
- 2. 1 \* CPU Smart Fan Connector, 2 \* Sys/Chassis Fan Connectors
- 3. 3 \* 9-Pin COM Port headers(COM2 Support RS422/RS485)
- 4. 1 \* IR header
- 5. 1 \* HDMI\_SPDIF header
- 6. 1 \* LVDS header
- 1. **BIOS**                            1. Award 4MB SPI Flash ROM
- 1. **Form Factor**                 1. Mini-ITX Embedded Motherboard(170mmx170mm)
- 1. **Temperature**                1. Operating within 0~60 centigrade
- 2. Storage within -20-85 centigrade

**Product Accessories**

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield
- 1x IDE cable