



69.95 EUR  
incl. 19% VAT, plus [shipping](#)

- M.2 NGFF !
- UMTS / 3G !
- LTE (EUROPE) !

Support: [Driver \(Windows\)](#) | [Firmware \(V14\)](#)

The ME906s-158 is a LTE module with NGFF interface , supporting LTE (FDD) B1/B2/B3/B5/B7/B8/B20/B28 ,Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA for Europe network coverage, low power consumption, Global Navigation Satellite System(GNSS), and European carrier certifications, enabling easier and more flexible design and integration into end devices. In addition, the ME906s-158 supports NGFF features to optimize performance, power consumption, and usability.

ME906s-158 is the ideal choice for Ultrabook, notebook, tablet etc.

<b>Manufacturer</b>	Huawei
<b>Model</b>	ME906s-158
<b>Unlocked</b>	Ready for use with global services. No contract required.
<b>Network Bands</b>	<ul style="list-style-type: none"> <li>• LTE (FDD) B1/B2/B3/B5/B7/B8/B20/B28</li> <li>Quad-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B5/B8</li> <li>Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz</li> <li>GPRS/EDGE: Multi-slot Class 12</li> </ul>
<b>Data Speed</b>	WCDMA PS: UL (384 kbps)/ DL (384 kbps) DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps) LTE FDD: UL (50 Mbps)/ DL (150 Mbps) @Bandwidth 20M (CAT4)

<b>Interface</b>	Antenna interfaces x 2 M.2 Socket 2 USB 2.0 interface high speed Power supply UICC interface
<b>Power Supply</b>	Supply voltage range:3.135V~4.4V (3.3 V recommended) Normal operation: -10°C to +55°C
<b>Temp Range</b>	Extended operation: -20°C to +70°C Storage: -40°C to +85°C
<b>GPS</b>	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass
<b>Dimensions</b>	<ul style="list-style-type: none"><li>• 42x30x2.3 mm</li></ul>
<b>Supported Systems</b>	Windows 7/Windows 8/Android 4.0 or above SIM Hotswap IPV6 BodySAR
<b>Special Features</b>	Ultrabook feature support(ACT, WiFi Offload , DPTF) Tunable Antenna Supporting MO and MT Supporting formats of PDU Point-to-point and cell broadcast
<b>Package Contents</b>	Huawei ME906s-158 NGFF Embedded Module.