



- | J7F2EDEN12G Specifications | |
|----------------------------|--|
| Processor | VIA C7 1.2 GHz processor |
| Chipset | VIA CN700 north bridge |
| | VIA VT8237R south bridge |
| System Memory | 1 DDR2 400/533 DIMM |
| | Up to 1GB memory size |
| VGA | Integrated VIA UniChrome AGP graphics |
| Expansion Slots | 1 PCI |
| Onboard IDE | 4 Ultra DMA 133 |
| Onboard Serial ATA | 2 SATA connectors |
| Onboard Floppy | 1 Floppy Port |
| Onboard USB | 8 USB 2.0 |
| Onboard LAN | VIA 6103 10/100 |
| Onboard Audio | ALC655 6 channel AC'97 codec |
| Onboard TV Out | VIA VT1622A TV encoder |
| Onboard 1394 | IEEE 1394 |
| Back Panel I/O | 1 1394 |
| | 1 RCA video |
| | 1 VGA port |
| | 2 USB 2.0 |
| | 1 LAN port |
| | 2 IEEE 1394 ports |
| | 1 serial ports |
| | 1 PS2 mouse port |
| | 1 PS2 keyboard port |
| | 3 audio jacks: line-out, line-in, and mic-in |

Onboard I/O Connectors	3 USB 2.0 connectors for 6 USB ports 1 parallel port 1 VGA port 2 serial ports 1 PS2 keyboard connector 1 PS2 mouse connector 1 floppy port Line-in/out/MIC audio ports
BIOS	Award BIOS LPC 4Mbit Flash memory
System Monitoring & Management	CPU temperature Modem ring wake up RTC Alarm Keyboard power on System temperature System voltage Fan speed
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)
Form Factor	Mini-ITX (17cm x 17cm)
Includes	ATA 133 flat cable (40 wire, 80 conductor, 3 connectors) CD SATA Cable Floppy Cable